



1-800-525-6828 • 1-706-253-7404 FAX: 1-706-253-7403 www.powersledge.com universalsales@powersledge.com



## **HD10000 DROP HAMMER**

The Hurricane drop hammer HD10000 is a high-production and low-maintenance drop-hammer for breaking concrete. Manufactured by Universal Impact Technologies, Inc., a Thunder Attachments company, the HD10000 is easily connected to a skid steer or an excavator and efficiently breaks concrete in industrial tear-outs, as well as parking lots, curbs, roads, runways and aprons, sidewalks up to 24-32 inches thick.\*

- EASY OPERATION reduces operator error and fatigue. The operator simply guides the skid steer in a straight line – and does not aim or continually reposition the hammer.
- SHOCK-FREE ground engagement platform system keeps the HD10000 grounded and focuses the shock into the pulverized concrete.
- · COMPACT DESIGN, light weight and easily transported.
- SIMPLE CONNECTION allows for easy attachment changes.
- LOW MAINTENANCE and minimal wear items enhance productivity.
- HIGH PRODUCTION due to the striking surface's broad face and coverage area.
- LOW INVESTMENT and high-volume production results in the lowest cost per yard ton of broken concrete when compared to traditional hydraulic hammer production.

## THE HD10000 ADVANTAGE

- Highest impact-to-weight ratio in the industry.
- The bolt-on-ground engagement end plate makes maintenance accessible and easy.
- Low maintenance because there are no points, bushings, seals and accumulators to replace.



HD10000 TECHNICAL DATA	
Impact Class	10,000 Foot Pounds
Impacts Per Minute	25
Total Impacts Per Minute	250,000 Foot Pounds
Hydraulic Pressure Minimum	2,200 PSI
Operating Height	8 Feet 11 Inches
Hammer Weight	3,360 Pounds
Maximum Concrete Thickness	24-32 Inches*

<sup>\*</sup> Performance varies based on reinforcement.